

články/ ks: 2 3 4
napětí/ V: 7.2 10.8 14.4

max. zatížení po dobu 30s: 22A
doporučený rozsah proudu: 10-20A

200W/10		APC elektro												
		6x4	6x5,5	7x5	8x4	8x6	9x4,5	9x6	9X7,5	10x5	10x7	6x4 GR	6,5x4 AE	6x5 AE
7.2 V	odběr/A	2.8	3.8	5.5	6.4	9.8	9.1	11.1	14.6	12.3	15.4	2.7	3.2	3.4
	otáčky/RPM	8310	8130	7920	7800	7200	7440	7020	6450	6870	6540	8280	8160	8160
	stat.tah/ kg	0.074	0.08	0.168	0.27	0.28	0.39	0.41	0.38	0.51	0.54	0.084	0.118	0.088
10.8 V	odběr/A	4.9	6.9	10.2	12.3	18.1	16.9	19.5	25.2	21.5	25.4	4.9	5.8	6.1
	otáčky/RPM	12060	11760	11190	10890	9750	10170	9420	8370	9060	8430	12120	11790	11820
	stat.tah/ kg	0.18	0.184	0.376	0.55	0.56	0.78	0.77	0.67	0.94	0.93	0.2	0.262	0.19
14.4 V	odběr/A	8	10.9	16.3	19.1	27.4	25.1	28.3		30.7		7.8	9.2	9.1
	otáčky/RPM	15690	15210	14130	13410	11640	12120	11220		10620		15690	15120	15270
	stat.tah/ kg	0.318	0.322	0.64	0.89	0.82	1.16	1.14		1.33		0.34	0.45	0.34

APC E - elektro; GR - Graupner šedivá; AE - Aeronaut